

Assembleon

Introduzione MG5

■ 5 in-line multi-heads & Double FID cameras ※



Name Richard Vereijssen/Marco van Oosterhout
Subject
Project MG-5 PA #/ Pricing
Feb 5, 2010



MG-5

Entry level 8 mm feeder

- New type of 8mm-feeder for optimal feeder usage
 - PA 2903/83 8mm-FT
 - 12mm width, without reel holder plate
 - Optimal for tape connection



MG-5 Basic machine

PA 1314/30

Specs for basic configuration:

- Optimal speed 20kCph, actual 10-12k
- 106 Fixed Feeder positions
- Max comp size 45x45mm (32~45 under conditions)
- Max comp. height 15mm
- Max PCB size L420 x W460mm
- Machine size L1,254xW1,440xH1,445mm

Including:

- Dummy feeders (needed for CE)
- Empty tape bins 2x
- Side Light for Ball Recognition
- PA 1314/50 Rear fixed feeder plate 59pos.
- PA 2904/91 Feeder Floating Sensor
- PA 1314/52 Reel Holder 2x 60pos Front+Rear
- PA 1314/53 Nozzle Station + nozzles
- PA 1314/54 Nozzle cleaning station
- PA 1314/57 First Aid Spare Parts kit
- PA 1314/58 Maintenance (Blue) tool box



3

Additional Options MG-5

- Conveyor extension to extent entrance and exit buffer length from 320 to 420mm
 - PA 2500/18 for MG-5
 - PA 2500/20 for MG-5 ATS
- PA 1314/51 Matrix type push up system
- PA 2969/27 Additional fiducial camera to extent board length from 420mm to 510
- PA 2506/42 Rear side LCD monitor, keyboard and mouse
- PA 2506/43 Touch panel Front & Rear side
- PA 2500/30 UPS system

Prezzi promozione 2010

- Pacchetto scontato netto promozionale per lancio MC5 (limitato a 10 unità) con:

- MC5 base
- Installazione
- Training 2 gg
- Trasporto e muletto scarico
- Nr. 60 caricatori da 8 mm

- **Prezzo complessivo: 90.000 euro**
- **Finanziabile con TREMONTI TER**

Assemblée

léon